

July 13, 2011

Illinois Environmental Protection Agency Permit Section Bureau of Land – #33 1021 North Grand Avenue East P.O. Box 19276 Springfield, IL 62794-9276



Re: 2018080001 - Winnebago County

Winnebago Landfill – Northern/Southern Units Annual Groundwater Flow Evaluation—2011-2012

Dear Agency Representative:

Pursuant to Condition VIII.20 of Permit No. 1991-138-LF, Modification 54, submitted herein is the facility groundwater flow evaluation. The condition states that annually, the operator shall prepare an evaluation of the groundwater flow direction and the hydraulic gradients at the facility using the groundwater surface elevations determined for each monitoring event. The groundwater flow has been evaluated for the past four quarters (third quarter 2011 through second quarter 2012). Potentiometric surface maps for each of the referenced quarters are provided herein.

If you have any questions regarding this notification, please contact Tom Hilbert at (815) 963-7516.

Sincerely

Teresa N. Sharp Environmental Scientist

TNS:tns:slm

Enclosure

cc: Tom Hilbert – Winnebago Reclamation Bernie Schorle – US EPA Region 5

levera n. Sharp

J:\1990\90-114 (Winnebago)\DOC\2012\2011-2012 flow evaluation\1991-138-LF\2012 GWFlow Eval Cvltr.doc Reporting



ILLINOIS ENVIRONMENTAL PROTECTION AGENCY SOLID WASTE REPORTING FORM

This form must be used as a cover for the following list of notices and reports required by the Illinois EPA's Bureau of Land, Permit Section. All reports must be submitted to the Illinois EPA's Bureau of Land Permit Section. This form must be used for Solid Waste facilities only. Reporting for Hazardous Waste facilities should be submitted on a separate Hazardous Waste Reporting Form. All reports submitted to the Illinois EPA's Bureau of Land Permit Section must contain an original, plus a minimum of two copies.

a minimum of two copies.			
Note:	This form may NOT be used for any request to modify the permit, sampling or operating procedures. Modification requests must be submitted separately in the form of a permit application. This form is not to be used with permit applications. Your permit will state whether the document you are submitting is required as a report or an application.		
Facilit	y Name: Winnebago Landfill - Northern and Southern Units	Site ID#:	2018080001
Check one of the following, identifying the contents of your submittal:			
	LPC-160 Forms ☐ Quarterly Groundwater Data ☐ Quarterly Leachate Data ☐ Annual Groundwater Data ☐ Annual Leachate Data	☐ Semi-Annu	nal Groundwater Data nal Leachate Data roundwater Data eachate Data
\checkmark	Annual Groundwater Flow Evaluation	□ We	ll Survey Data
	Well Construction Forms and Boring Logs	☐ We	ll Abandonment Forms
	Notice of Observed Increase in Groundwater Notice of Intent to Perform Confirmation Procedures (Re-sampling) in Groundwater		
	Notice of Confirmed Increase of Groundwater Exceedence from Re-sample		
	Notice of Methane Exceedences		
	Annual Facility Report (per 35 Ill. Adm. Code 813.504) and Gas Monitoring Report		
	Annual Certifications per 35 Ill. Adm. Code 813.501		
Other (identify): Not to be used for Permit Applications			

ANNUAL GROUNDWATER FLOW EVALUATION

WINNEBAGO LANDFILL - PERMIT NO. 1991-138-LF

2018080001 - WINNEBAGO COUNTY

In accordance with Condition VIII.20 of Permit No. 1991-138-LF, Modification 54, an evaluation of the groundwater flow and hydraulic gradients for the Northern and Southern Units of Winnebago Landfill has been completed for third and fourth quarters of 2011 and first and second quarters of 2012. The attached potentiometric surface maps illustrate the general groundwater flow direction and gradients for the Northern and Southern Units. Also shown in the attached potentiometric maps is the North Expansion Unit (NEU). The NEU is operated under a separate Permit No. (2006-221-LF). A separate Annual Groundwater Flow Evaluation has been submitted for Permit No. 2006-221-LF. The unit is shown on the potentiometric surface maps because it monitors the same aquifer system as the Northern and Southern Units of Winnebago Landfill and provides a complete illustration of the groundwater flow characteristics.

The potentiometric surface data used in construction of the contour maps were obtained from both shallow and deep wells, as the screen intervals are located within deposits that are hydraulically connected.

One hydraulic gradient has been calculated for each quarter. Based on the distance between the selected wells and the change in groundwater elevation, the steepest gradient is represented. The gradient becomes very flat in areas surrounding Killbuck Creek, illustrated by greater distances between contours.

Gradients calculated from wells G09M to G51S (third quarter 2011) and G09M to G184 (fourth quarter 2011 through second quarter 2012) ranged from 0.016433 to 0.018541 during the four quarters of this review. The average gradient for the four quarters was calculated as 0.01764. The gradient is shown on each potentiometric surface map illustrating the flow path used to determine the values.

Based on the evaluation of groundwater flow, the existing monitoring well network is appropriate to adequately monitor the facility groundwater. Therefore, no modifications to the monitoring well network are necessary.







